



Last Updated: Thursday, 29 January 2009



**OPTION AUDIO 2 CH Amplifier**

**OAA160**

|  | <b>Specifications</b>   |
|--|-------------------------|
| <b>RMS power at 14.4V (4Ω Load)</b>    | 160W x 2CH              |
| <b>RMS power at 14.4V (2Ω Load)</b>    | 190W x 2CH              |
| <b>RMS power at 14.4V (4Ω Load)</b>    | 350W x 1CH              |
| <b>Input level</b>                     | 0.2 ~ 5V                |
| <b>Two Channel Input Mode</b>          | YES                     |
| <b>Group A Filter Mode</b>             | HPF-FULL-LPF            |
| <b>Group B Filter Mode</b>             | N/A                     |
| <b>Group A LPF</b>                     | 50~750Hz                |
| <b>Group A HPF</b>                     | 50~750Hz                |
| <b>Group B LPF</b>                     | N/A                     |
| <b>Group B HPF</b>                     | N/A                     |
| <b>Frequency Response</b>              | 10~25KHz                |
| <b>THD at 4 Ω Load 30% Rated Power</b> | <0.02%                  |
| <b>S/N Ratio</b>                       | >090dB                  |
| <b>Minimum Load</b>                    | 2 Ω                     |
| <b>Overload Protect Systems</b>        | YES                     |
| <b>Overheat protect temperature</b>    | 80°C / 176°F            |
| <b>Components &amp; PCB</b>            | SMD & Double side board |
| <b>Transparent isolation connector</b> | YES                     |
| <b>Height (mm)</b>                     | 53                      |
| <b>Width (mm)</b>                      | 228                     |
| <b>Length (mm)</b>                     | 240                     |